


**MVE 800/1E-60A0 (EE60080060A0JA0000)****3 PH - 6 poles - 1000 RPM - 220-240/380-415 V - 50 Hz**

Working moment (Kg*cm)	Unbalance (Kg*cm)	Centrifugal force (Kg)	Nominal voltage (V)	Input power (kW)	Current (A)	Power factor	Ia/In
137,37	68,69	767	220-240/380-415	0,75	Δ 2,46 Y 1,42	0,76	3,4



*Technical drawings are illustrative purposes only, please refer to 2D/3D drawings available on "FINDER" app. Contact us for more information.

OVERALL DIMENSIONS (mm)

Weight (Kg)	A	B	G	Holes number	C	D	E	F	H	I	L	M	N
60,4	140	190	17	4	446	230	260	26	124	240	218	112	222

TECHNICAL FEATURES

Type of grease	Greased for life	Screw	Washer	Clamping torque (Nm)	Cable type	Cable gland
Please refer to the label on the motorvibrator	Yes	M16	17 x 30 mm	185	4G4 120°C	M25 120°C

BEARINGS LIFE HOURS

Bearing model	Type	100% C.F	80% C.F	50% C.F
NJ 308		>100000	>100000	>100000

CERTIFICATION

ATEX II2 D Ex tb IIIC Tx Db IP66

IECEX Ex tb IIIC Tx Db IP66

CLASS II DIV.2 GROUP F,G T4

Ex tb IIIC Tx Db IP66

[Tx Size Micro, 10-30:100°C - Tx Size 40-91:135°C]

CONF.TO UL1004-3, UL1004-1, UL 60079-0, UL60079-31

CERT. CSA C22.2 No.100, CSA C22.2 No.77, CSA C22.2N.60079-0, CSA C22.2N.

60079-31

T.Amb -20/+40°C



